

# Quik Drive™ PRO300S System

**MULTI-FIX** WA



Decking | Subfloor | Underlay | Cladding | Sheathing

CLICK LOGO FOR  
WERE TO BUY

## Save Time and Money with Faster Installation Speeds and Consistent Performance



### Features:

- Expanded depth settings for high-density flooring materials <sup>1</sup>
- Reversible and replaceable non-skid teeth <sup>2</sup>
- Uniform toenailing and countersink on smooth surfaces
- Sure-grip guide tube increases stability for a broad range of screws <sup>3</sup>
- Rigid strip collation prevents jamming <sup>4</sup>
- Extension enables stand-up driving to save time and reduce worker fatigue <sup>5</sup>
- QuikLock™ coupling allows for easy assembly and disassembly so system can be used without extension pole <sup>6</sup>
- Built-in bit wrench makes bit changes quick and easy <sup>7</sup>
- Drive 8 – 10 gauge and 40mm to 75mm Quik Drive screws

**PDECKNC-RC** (sold separately)

*The decking nose clip positions the screw on the deck board and positions it over the joist for an easy, uniform installation from a standing position.*

# PRO300S System







**PRO300SKA includes:**

- PRO300S Attachment (also sold separately)
- Extension
- Screw quiver
- Rugged toolbox
- Adaptors; BOA1G2, MAA3G2, HIAG2  
(Suit Bosch® GSR625TE, Makita® FS2300 & FS2500, Hitachi® Screwguns)  
Adaptors for DeWalt®, Hilti® and Milwaukee®, screwdriver motors are also available.

*For more information on screwdriver motors and RPM recommendations per application, please visit one of our websites for your region.*

### Quik Drive® PRO300S System Options

	System Options	Model No.
	Makita® 2500 rpm screwdriver motor	PRO300SM25KA
	Bosch® 2500 rpm screwdriver motor	PRO300SB25KA
Parts		
	PRO300S Attachment only	QDPRO300SG2
	Replacement attachment mandrel	PMANDREL75
















*Get the right adaptor for your model screwgun by contacting your Simpson Strong-Tie representative.*

# Screws available for the PRO300S System

**MULTI-FIX** WA



Driver bits supplied with every box of screws • All genuine Quik Drive screws come in strips of 30 screws.

 <p><b>Strong-Drive™ WSNTL SUBFLOOR Screw</b> Ribbed flat head, twin lead thread, sharp point, yellow zinc</p> <p><b>WSNTLA134SA:</b> 8g x 45mm  <b>WSNTL2LSA:</b> 8g x 50mm  <b>WSNTLA2SA10:</b> 10g x 50mm (Complies with AS 1860)  <b>WSNTLG2SA:</b> 8g x 50mm (Class 3 galvanised)  <b>WSNTL212SA:</b> 8g x 65mm  <b>WSNTLG212S:</b> 8g x 65mm (Class 3 galvanised)  <b>WSNTL3S:</b> 8g x 75mm  <b>WSNTLG3S:</b> 8g x 75mm (Class 3 galvanised)</p> <ul style="list-style-type: none"> <li>• Drive up to 40% faster than single thread screws</li> </ul> <p>QRS3</p>	 <p><b>Deck-Drive™ BFHSD BI-METAL Screw</b> Ribbed flat head, 16 TPI, #2 drill point with wings, 316 stainless steel bi-metal</p> <p><b>SSBFHSD2SA:</b> 10g x 50mm</p> <ul style="list-style-type: none"> <li>• Zinc coated to prevent dissimilar metal reaction</li> <li>• Suitable for 1.2mm – 2.4mm steel thickness</li> </ul> <p>QRS2</p>
 <p><b>SSWSC WOOD Screw</b> Flat head with nibs, coarse thread, type 17 point, 305 stainless steel</p> <p><b>SSWSC2BSA10:</b> 10g x 50mm</p> <ul style="list-style-type: none"> <li>• High corrosion resistance</li> <li>• Type 17 point for easier driving</li> </ul> <p>QRS3</p>	 <p><b>CBSD WINGED SELF DRILLING Screw</b> Ribbed flat head, 18TPI, #2 drill point with wings, Class 3 mech. gal. coating</p> <p><b>CBSDG158SA:</b> 8g x 42mm  <b>CBSDGL158SA:</b> 10g x 42mm  <b>CBSDGL214SA:</b> 10g x 55mm  <b>CBSDGL3SA:</b> 10g x 75mm  <b>CBSDZ158SA:</b> 8g x 42mm (Yellow zinc – ZA only)</p> <ul style="list-style-type: none"> <li>• Engineered to fasten sheet flooring and timber to steel framing. (0.8 – 2.4mm 8g, 1.2 – 3mm 10g)</li> </ul> <p>QRS2</p>
 <p><b>Deck-Drive™ DSV WOOD Screw</b> Rimmed flat-head with nibs, coarse thread, sharp point, Quik Guard® coating</p> <p><b>DSVT2S:</b> 10g x 50mm  <b>DSVT212S:</b> 10g x 65mm</p> <ul style="list-style-type: none"> <li>• Designed to withstand the swelling and shrinkage that is common with softwood timber decking.</li> </ul> <p>QRS3</p>	 <p><b>CBSDHG COMPRESSED CEMENT SHEET Screw</b> Ribbed flat head, 16 TPI, #2 drill point with wings, Class 3 mech. gal. coating</p> <p><b>CBSDHG158SA:</b> 10g x 42mm  <b>CBSDHG214SA:</b> 10g x 55mm</p> <ul style="list-style-type: none"> <li>• Engineered to fasten compressed cement sheet to steel framing. (1.2 – 3mm steel)</li> </ul> <p>QRS3</p>
 <p><b>Deck-Drive™ DHW HARDWOOD Screw</b> Compact head, coarse thread, winged, hardwood drill point</p> <p><b>DHWG60SA:</b> 10g x 60mm (Class 3 galvanised)  <b>SSDHW60SA:</b> 10g x 60mm (305 stainless steel)</p> <ul style="list-style-type: none"> <li>• Wings for countersinking</li> <li>• Drill point reduces pre-drilling &amp; timber splitting</li> </ul> <p>QRS2</p>	 <p><b>PPSD PLYWOOD-TO-STEEL Screw</b> Flat head with nibs, 18 TPI, pilot point, #2 drill point, yellow zinc</p> <p><b>PPSD11516SA:</b> 8g x 48mm</p> <ul style="list-style-type: none"> <li>• Engineered for steel framing up to 2.4mm – prevents wood and plywood materials (up to 19mm) from “riding up” threads</li> </ul> <p>QRS3</p>
 <p><b>Deck-Drive™ DHSD HARDWOOD Screw</b> Raised countersinking head, coarse thread, hardwood drill point, 305 stainless steel</p> <p><b>SSDHSD50S:</b> 10g x 50mm  <b>SSDHSD60S:</b> 10g x 60mm</p> <ul style="list-style-type: none"> <li>• Penetrates hardwood products with ease</li> <li>• Unique drill point reduces splitting without pre-drilling</li> </ul> <p>QRS2</p>	 <p><b>WSCBGA158SA CEMENT SHEET AND UNDERLAY Screw</b> Wafer head with nibs, coarse thread, Type 17, Class 3 mech. gal. coating</p> <p><b>WSCBGA158SA:</b> 8g x 42mm</p> <ul style="list-style-type: none"> <li>• Cement sheet to timber</li> </ul> <p>QRS2</p>
 <p><b>Composi-lok™ COMPOSITE-DECKING Screw</b> Cap head, coarse thread, sharp point, Quik Guard® coating</p> <p><b>HCKDCLB212S:</b> 9g x 65mm (Brown)  <b>HCKDCLG212S:</b> 9g x 65mm (Grey)  <b>HCKDCLR212S:</b> 9g x 65mm (Red)  <b>HCKDCLT212S:</b> 9g x 65mm (Tan)  <b>HCKSSDCL212S:</b> 9g x 65mm (305 stainless steel)</p> <ul style="list-style-type: none"> <li>• Cap head prevents any mushrooming</li> </ul> <p>QRS2</p>	 <p><b>SS3DSC BUGLE-HEAD WOOD Screw</b> Bugle head, coarse thread, type 17, 305 stainless steel</p> <p><b>SS3DSC212BS:</b> 10g x 65mm  <b>SS3DSC3BS:</b> 10g x 75mm</p> <ul style="list-style-type: none"> <li>• Type 17 point for easy, straight drive</li> </ul> <p>QRS3</p>
 <p><b>Deck-Drive™ DCSD COMPOSITE-TO-STEEL Screw</b> Cap head, 16 TPI, #2 drill point, Quik Guard® coating</p> <p><b>DCSD238SBR01:</b> 10g x 60mm (Brown)  <b>DCSD238SGR01:</b> 10g x 60mm (Grey)  <b>DCSD238SRD01:</b> 10g x 60mm (Red)  <b>DCSD238STN01:</b> 10g x 60mm (Tan)</p> <ul style="list-style-type: none"> <li>• Unique fluted pilot point clears excess composite material</li> <li>• Cap-head prevents mushrooming</li> </ul> <p>QRS2</p>	 <p><b>DTH TRIM HEAD Screw</b> Trim head with nibs, 9 TPI, type 17 point, Class 3 mech. gal. coating, #2 square drive</p> <p><b>DTHG2SA:</b> 8g x 50mm  <b>DTHG212SA:</b> 8g x 65mm  <b>DTHQ3S:</b> 8g x 75mm (Quik Guard® coating)</p> <ul style="list-style-type: none"> <li>• Type 17 point for easy, straight drive</li> <li>• Trim head for neat appearance</li> </ul> <p>QRS2</p>
	 <p><b>SSDTH TRIM HEAD Screw</b> Trim head, 10 TPI box thread, sharp point, 305 stainless steel, #2 square drive</p> <p><b>SSDTH2SA:</b> 7g x 50mm  <b>SSDTH212SA:</b> 7g x 65mm</p> <ul style="list-style-type: none"> <li>• High corrosion resistance</li> </ul> <p>QRS2</p>

Note: Stainless-steel screws may require pre-drilling in certain high-density materials. Class 3 mechanically galvanised coating – complies with AS 3566