

A new breed of ladder



www.gorillaladders.com.au

Contents

Who are we? Gorilla product features 4 - 5**Domestic range** 6 - 7Industrial 120kg 8 - 1112 - 24Industrial 150kg* Specialised access 25 - 2627 - 29Accessories Choosing your ladder 30 Safe use of your ladder 31 **Details and addresses** 32



* Fibreglass Extension Ladders 130kg Single Builders Ladders 140kg

Who are we?

Gorilla manufactures the highest quality products available, representing outstanding value across a broad range of applications.

Gorilla ladders are manufactured in the largest ladder manufacturing plant in the world, to Australian & New Zealand Standards. All Gorilla research and development is conducted in Australia, with designs tested and modified in Australia & New Zealand.

Gorilla manufactures a range of patented products, including the Gorilla Stabiliser and Gorilla Brace which can increase ladder safety. Unique products such as the telescoping aluminium plank and Gorilla Bumpers are all part of the dynamic range that Gorilla is proud to bring to market.

Images used across the catalogue may differ from actual product due to changes in specification which occur from time to time. Ladder specifications are believed to be correct at time of printing and subject to change without notice.

Product Features

Top Cap Organiser

On Aluminium and Industrial Fibreglass single sided ladders.



Anti-Slip Treads

Minimises slipping. Featured on all Gorilla ladder designs.



Resin Bracing System

Patented resin brace on Industrial 150kg models 1.8m (6ft) and over (excludes extension ladders).



Roll Locked D-Shaped Rungs

Featured on Industrial extension ladders for added strength and durability.



Stabiliser Mounting

Factory produced mounting holes allow for easy fitting of stabiliser. Mounting holes on most Gorilla ladders 1.8m and over.




Internal Spreader

Packs away to prevent fouling.



Non-Slip Heavy Duty Platform

Large non-slip platform surface for added safety when working at heights. Platform featured on Gorilla platform ladders.



Handrail

Heavy duty aluminium handrail fitted to all Gorilla platform ladders (positioned 900mm from platform).



Domestic

All domestic ladders are approved to AS/NZS1892.1, domestic rating. Please refer to each product for load rating. These ladders provide a dependable, high quality product to the domestic user.

Domestic ladders cover most home user applications, and include features such as;

- · non-slip feet
- · AS/NZS standards approval
- · lightweight, high strength aluminium.

Most Gorilla ladders 1.8m (6ft) and over are supplied with factory mounting points for the Gorilla patented Stabiliser, as noted beside each product.



(see page 27 for further information)







Material: Aluminium 120kg Domestic

Height: 1.8-3.2m (6-10ft) Weight: 10.8kg Code: DM006-D

> Features: Cross-Braced Spreader Lightweight Non-Slip Stabiliser Ready



Contractor industrial ladders are approved to AS/NZS1892.1, 120kg industrial rating. These ladders provide a dependable, high quality, durable product to the trade and serious DIY user.


Gorilla Contractor products comply to AS/NZS standards at the industrial level, meaning these products can be used in commercial environments.

Contractor ladders are designed with heavy duty usage in mind, and are manufactured with features such as aluminium top caps and additional stile/tread bracing.

All Gorilla ladders 1.8m (6ft) and over are supplied with factory mounting points for the Gorilla patented Stabiliser* (see page 27 for further information).







Ma H

Material: Aluminium 120kg Industrial

> Height: 0.9m (3ft) Weight: 5.1kg Code: SM003-C

Height: 1.8m (6ft) Weight: 9.6kg Code: SM006-C

Height: 2.4m (8ft) Weight: 14kg Code: SM008-C

Features: Cross-Braced Spreader Lightweight Non-Slip Alum Top Cap

SM006-C and SM008-C Stabiliser Ready





Material: Aluminium 120kg Industrial

Height: 0.6-0.9m (2-3ft) (390 x 1150mm Platform) Weight: 8.0kg Item No: 0861872 Code: MW105-C

Platform tested to AS/NZS 182.1:9.3.3



Aluminium Gorilla Mighty 15

Material: Aluminium 120kg Industrial

A-frame heights: 1.2-2.1m Extension heights: 2.7-4.5m Weight: 19.5kg Code: MM15-I

Features:
Multi-purpose ladder
(4 configurations)
A-frame
Extension
Uneven A-frame (stainway)
Trestle
MM15 includes
factory fitted wheels

New Platform and Project Tray accessory now also available. See page 25 for more details.



Double Sided Step Ladder

Material: Fibreglass 120kg Industrial

> Height: 1.2m (4ft) Weight: 7.7kg Code: FSM004-C

Height: 1.8m (6ft) Weight: 10kg Code: FSM006-C

Features: Non-Slip Alum Top Cap Cross-Braced Spreader Stabiliser ready



All industrial ladders are approved to AS/NZS 1892.1/AS/NZS1892.3, industrial rating. Please refer to each product for load rating. These ladders provide the highest strength product available, ready for use by the serious trade user, in commercial environments.

Industrial ladders are designed with heavy duty usage in mind, and are manufactured to survive every-day use.

Industrial products feature the patented Gorilla Resin Bracing System to increase torsional strength and decrease lower-stile damage.

All Gorilla ladders 1.8m (6ft) and over are supplied with factory mounting points for the Gorilla patented Stabiliser* (see page 27 for further information).



Single Sided Step Ladder Material: Aluminium 150kg Industrial Height: 1.8m (6ft) Weight: 8.9kg Code: M006-I Height: 2.4m (8ft) Weight: 12.2kg Code: M008-I Features: Cross-Braced Spreader Non-Slip Alum Top Cap Stabiliser Ready Patented Resin Bracing System



Material: Aluminium 150kg Industrial

Height: 0.9m (3ft) Weight: 5.1kg Code: SM003-I

Height: 1.2m (4ft) Weight: 7.1kg Code: SM004-I

Height: 1.8m (6ft) Weight: 11.3kg Code: SM006-I

Height: 2.4m (8ft) Weight: 16.7kg Code: SM008-I

Height: 3.0m (10ft) Weight: 21kg Code: SM010-I

Features: Cross-Braced Spreader Non-Slip Alum Top Cap

SM006-I, SM008-I and and SM010-I Stabiliser Ready, Patented Resin Bracing System

* Fibreglass Extension Ladders 130kg Single Builders Ladders 140kg



Cross-braced spreader for premium stability

Dual Purpose (Double Sided)

Material: Aluminium 150kg Industrial

Height: 1.8-3.3m (6-11ft) Weight: 10.7kg Code: DM006-I

Height: 2.1-3.9m (7-13ft) Weight: 12.16kg Code: DM007-I

Height: 2.4-4.5m (8-15ft) Weight: 14.28kg Code: DM008-I



Extension Ladder

Material: Aluminium 150kg Industrial

Height: 2.4-3.9m (8-13ft) Weight: 11kg Code: EL8/13-I

Height: 3.1-5.3m (10-17ft) Weight: 13.4kg Code: EL10/17-I

Height: 3.7-6.5m (12-21ft) Weight: 15.8kg Code: EL12/21-I

Features: Single-Rope Pull and Release Strong Roll-locked D-Rungs Stabiliser Ready



Single Builders Ladders

Material: Aluminium 140kg Industrial

Height: 4.3m (14ft) Weight: 9.9kg Code: SBL014-I

Height: 2.4m (8ft) Weight: 5.7kg Code: SBL008-I

Height: 4.6m (15ft) Weight: 10.2kg Code: SBL015-I

Height: 2.7m (9ft) Weight: 6.4kg Code: SBL009-I

Height: 4.9m (16ft) Weight: 11.6kg Code: SBL016-I

Height: 3.1m (10ft) Weight: 7.4kg Code: SBL010-I

Height: 5.5m (18ft) Weight: 12.1kg Code: SBL018-I

Height: 3.7m (12ft) Weight: 8.3kg Code: SBL012-I

Height: 6.1m (20ft) Weight: 13.4kg Code: SBL020-I

Features: Strong Roll-Locked D-Rungs Non-slip Non-marking feet

Note: Optional hooks for use with scaffold



Extension Ladder

Material: Fibreglass 130kg Industrial

Height: 3.1-5.3m (10-17ft) Weight: 20.1kg Code: FEL10/17-I

Height: 3.7-6.5m (12-21ft) Weight: 23.4kg Code: FEL12/21-I

Features: Roll-locked D-Rungs, Single-Rope Pull & Release, Stabiliser Ready.

Note: Fibreglass extension ladders now also available with factory fitted Pole Mount. Product codes FELP10/17-1 & FELP12/21-1 See P25 for more details.

* Fibreglass Extension Ladders 130kg Single Builders Ladders 140kg

Platform Ladder

Material: Aluminium 150kg Industrial

> Height: 0.9m (3ft) Weight: 14.8kg Code: PL003-I

Height: 1.2m (4ft) Weight: 16.6kg Code: PL004-I

Height: 1.8m (6ft) Weight: 20.9kg Code: PL006-I

Features: 900mm hand rail meets OH&S requirements Non-slip treads and platform surface Patented Resin Bracing System





Also available on request: Hand rail work tray (PL-TRAY), Platform toe stop (PL-TOE) and Safety boom (PL-BOOM)

Single Sided Step Ladder

Material: Fibreglass 150kg Industrial

> Height: 1.8m (6ft) Weight: 11.6kg Code: FM006-I

> Height: 2.4m (8ft) Weight: 15.1kg Code: FM008-I

Height: 3.0m (10ft) Weight: 19.6kg Code: FM010-I

Non-Slip, Alum Top Cap Tool Organiser (pictured on front cover) Cross-Braced Spreader Stabiliser Ready Patented Resin Bracing System

Double Sided Step Ladder

Material: Fibreglass 150kg Industrial

Height: 0.9m (3ft) Weight: 5.7kg Code: FSM003-I

Height: 1.2m (4ft) Weight: 8.6kg Code: FSM004-I


Height: 1.8m (6ft) Weight: 13.3kg Code: FSM006-I

Height: 2.4m (8ft) Weight: 17.8kg Code: FSM008-I


Height: 3.0m (10ft) Weight: 24.6kg Code: FSM010-I

Height: 3.6m (12ft) Weight: 31.8kg Code: FSM012-I

Non-Slip Alum Top Cap Cross-Braced Spreader



Patented Resin Bracing System



Platform Ladder

Material: Fibreglass 150kg Industrial

> Height: 0.6m (2ft) Weight: 12.3kg Code: FPL002-I

Height: 0.9m (3ft) Weight: 15.9kg Code: FPL003-I

Height: 1.2m (4ft) Weight: 17.04kg Code: FPL004-I

Height: 1.5m (5ft) Weight: 17.8kg Code: FPL005-I

Height: 1.8m (6ft) Weight: 22.3kg Code: FPL006-I

Height: 2.4m (8ft) Weight: 36kg Code: FPL008-I

Features:
900mm hand rail meets
OH&S requirements
Non-slip treads
and platform surface
Patented Resin
Bracing System



Wheel Kits Available on request








Also available on request: Hand rail work tray (PL-TRAY), Platform toe stop (PL-TOE) and Safety boom (PL-BOOM)

Dual Purpose Ladder

Material: Fibreglass 150kg Industrial

Height: 1.8-3.2m (6-10ft) Weight: 12.8kg Code: FDM006-I

Height: 2.1-3.8m (7-12ft) Weight: 14.8kg Code: FDM007-I









Heavy Duty Mighty Plank

Material: Aluminium 260kg Industrial

Length: 2.4-3.9m (8-13ft) Platform Width: 450mm Weight: 14kg Code: PLANK01-I450

Features: Aluminium Box Section Closes up for easy transport Telescopic



Paint Platform

Material: Aluminium 150kg Industrial

Height: 0.6-0.9m (2-3ft) Length: 1150mm Platform Width: 450mm Weight: 8.62kg Code: MW105-I450



Features: Large platform area Positive locks Multi-heights

Platform tested to AS/NZS 1892.1:9.3.3





Heavy Duty Extendable Work Platform

Material: Aluminium 150kg Industrial

Height: 0.5m-0.9m (1.8-2.9ft) Length: 1.6m-2.1m (5.5-6.9ft) Platform Width: 450mm Weight: 20.8kg Code: MW010-I450



Features: Extendable platform area Positive Locks Multi-heights



Work Platform

Material: Fibreglass 150kg Industrial

Height: 0.6m (2ft) Length: 1150mm Platform Width: 450mm Weight: 8.2kg Code: FMW105-I450



Features: Large platform area Positive locks

Platform tested to AS/NZS 1892.1:9.3.3



Heavy Duty Extendable Work Platform

Material: Aluminium 150kg Industrial

Height: 0.5m-0.9m (1.8-2.9ft) Length: 1.6m-2.1m (5.5-6.9ft) Platform Width: 295mm Weight:15.9kg Code: MW010-I

> Features: Extendable platform area Positive Locks Multi-heights



Gorilla Heavy Duty 3 Stair Material: Aluminium 150kg Industrial Height: 660mm Length: 820mm Weight: 8.5kg Code: GOR-3STAIR Features: 150kg load rated Lightweight Strong aluminium steps Wheels Compact folding design AS/NZS 1892.1:1996, Clauses 9.3.1, 9.3.2, & 9.3.31

Gorilla Safety Step

150kg Industrial

Height: 370mm Length: 510mm Weight: 3.3kg Code: GOR-STEP

> Features: 150kg load rated High grip tape







Order Picking Ladder

Material: Aluminium 200kg Industrial

Height to platform: 0.9m Weight: 33.3kg Code: GOP03

Height to platform: 1.2m Weight: 34.6kg Code: GOP04

Height to platform: 1.5m Weight: 38.2kg Code: GOP05

Height to platform: 2.1m Weight: 46.2kg Code: GOP07

Features: Large platform surface: 600mm (wide) x 585mm (deep) Patented raise/lower mechanism provides effortless and reliable activation. Optional accessories: 'Team members only' · Safety Boom (providing back support for added safety) · Work Tray

> Supplied flat packed ready to assemble.



GOP-HANDRAIL Fits all sizes of GOP order picker. Included fixings. Fits to Order Pickers to allow step through access. Ideal to access truck trays and elevated walk ways.

* Fibreglass Extension Ladders 130kg Single Builders Ladders 140kg



Designed By: NO BOLT

Scaffold

The Gorilla Expanda Scaff has been specially designed by one of Australia's leading scaffolding companies (No Bolt) to incorporate strength, durability and most importantly flexibility. The Expanda Scaff incorporates a unique design that allows you to expand up and out by adding additional free standing core packs, making it incredibly versatile.

Material: Aluminium 225kg per width of scaffold

Core Pack Code: GS-01

Contents: 4 x Horizontals, 1 x Diagonal Brace, 2 x End Frames, 1 x Trapdoor Tray & 4 x 125mm (6") Locking Castors.

Height:

Number of core packs Number of riser packs 0 2 Safe Platform Height 2.1m 0 9m 3 7m Working Height 2.4-2.7m 3.6-3.9m 5.2-5.5m



Core Pack Code: GS-01

Riser Pack Code: GS-01A

Outrigger Pack Code: GS-02

Joiner Pack Code: GS-03

Kickboards (4 pack) Code: GS-KICKB

Adjustable Castors Code: GS-S879B

Features: Workcover design registered

Picture (left) shows Expanda Scaff in full height configuration (using 1 Core Pack and 2 Riser Packs). Also pictured are Outriggers and Ladder.

> GS-01A Riser Pack (contains 4 Horizontal, 1 Diagonal Brace and 2 End Frames).

Working heights are generally measured in front of user in the space between their chest and shoulders. These heights are intended as a guide only as the height of the user will greatly vary these measurements.

ASL-009-I ladder to suit 2 high ASL-015-I ladder to suit 3 high



Specialised Access

Heavy Duty Platforms Material: Aluminium Rating: 150kg Industrial Sizes available: 600mm, 900mm, 1200mm, 1500mm, 1800mm, 2100mm, 2400mm, 2700mm and 3000mm. Features: Heavy duty platform for commercial use.

Custom Design Platforms

Specially engineered platforms can be made to suit just about any application.



Accessories





Gorilla Outrigger Material: Aluminium Code: AS-400 Features: Spring loaded locking mechanism for easy fit and removal. Provides additional stability for extension ladders. Convenient paint bucket hook. 1150mm wide span and 250mm stand off.

Gorilla Pole Mount

Material: Metal/rubberised plastic

Code: POLEM-01

Features: Fits Gorilla fibreglass extension ladders. Pivoting brace, restraining strap and rubberised pole grip.


> Can be supplied factory fitted with extension ladder.

Material: Metal/Plastic Code: MM-WHEELS

Multi-Purpose Wheel Kit



Note: MM-WHEELS shown with MM15-I ladder (above) sold separately.



Gorilla Bumper

Material: Soft rubberised plastic

Code: LB-01



Features: Fits most extension ladders Reversible for extra long life Durable heavy duty construction.



Choosing your ladder

Safe use of your ladder

Step Ladder

Choose a ladder 0.6m shorter than the height you wish to reach

Some examples:

Height to reach Ladder height

1.8m 1.2m ladder

2.4m 1.8m ladder

3.0m 2.4m ladder


Extension Ladder

Choose a ladder 1.0m longer than the height you wish to reach

Some Examples:

5 0m

Height to reach Ladder height
2.4m 3.4m ladder min
3.7m 4.7m ladder min



Aluminium or Fibreglass?

As a general rule, fibreglass ladders are recommended and in most cases mandatory when working in an electrical environment. A fibreglass ladder provides isolation between the user and earth, reducing (but not eliminating) the risk of electrocution.

6 0m ladder min

Aluminium ladders provide little electrical isolation for users, and are therefore not recommended for use in electrical environments.

Aluminium ladders are lighter than fibreglass, and are perfect for use in all non-electrical environments

ALWAYS inspect your ladder for damage prior to use – **DO NOT** use any ladder which is damaged.

ALWAYS be aware of your environment before setting up – check for hazards such as power cables, moving vehicles and doors.

ALWAYS wear appropriate, fully-enclosed footware.

ALWAYS face the ladder when ascending/ descending.

ALWAYS read ALL instructions present on ladder before use.

NEVER leave your ladder unattended – children may ascend and fall.

Step Ladders

ALWAYS use in the fully open position, with spreader mechanisms engaged.

NEVER stand on the top step.

ALWAYS keep body centred within the stiles of the ladder.

ALWAYS ensure ladder is positioned with all feet in contact with the ground and the surface is firm and level.

Extension Ladders

ALWAYS extend top of ladder >1.0m beyond the top support point.

ALWAYS lean your ladder at an angle of 1:4 – for each 4m your ladder is extended, it should be 1.0m out from the top support point.

ALWAYS ensure that the ladder feet and top support point are secure and cannot slip.

Accessories

ALWAYS read and follow usage directions.

Warranty

1 Year limited warranty against manufacturers faults and defects.

Proof of purchase is required. Warranty does not cover wear and tear or product misuse.



A new breed of ladder

GORILLA LADDERS AUSTRALIA

National hotline 1300 362 393 Fax 1300 135 069

National Sales sales@gorillaladders.com.au

Web

www.gorillaladders.com.au

Head Office

Gorilla Ladders Unit 1, 1 Federation Way Chifley Business Park Mentone VIC 3194

GORILLA LADDERS NEW ZEALAND

National Hotline 09 276 4071 Fax 09 276 1798

NZ Sales

sales@gorillaladders.co.nz

Web

www.gorillaladders.co.nz

Head Office

Harkness & Young PO Box 11344 Ellerslie, Auckland



www.gorillaladders.com.au