## Nylon Fasteners

## HobSpec DataSheet

## **Nylon Fasteners**



PVDF	DA.	PA6 / 6.6 / 66	В	POM	PE -LD	PE - HD	Material
							Cold Water
							Hot Water
							Diluted acid
							Concentrated acid
							Oxidized acid
							Hydrofluoric acids
							Diluted potassium
							Concentrated potassium
							Inorganic bases
							Dry halogen
							Hydrocarbons
							Hydrocarbons (chlorinated)
							Alcohols
							Ester
							Ketone
							Ether
							Aldehyde
							Amino acids
							Organic acids
							Aromatic hydrocarbons
							Petrol
							Mineral oils
							Greases and oils
							Hydrocarbons (non-saturated chlorinates)
							Oil of turpentine
0.03	0.1 - 0.2	1.3 - 1.9	0.01 - 0.03	0.22 - 0.25	<0.01	<0.01	Humidity absorbtion % to ASTM d 570

Good Resistance

Limited Resistance

Not Resistant

Disclaimer: While every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering, its agencies and employees, disclaim any and all liability to any person in respect of anything or the consequences of anything done or omitted to be done in reliance upon the whole or any part of this document.